


7	6





2	1	
Desc.		Auth.
Initial Drawi	ng	E.Z

) /	Control Voltage	Steam Flowrate (Ibs/hr)	Feed Water Consumption (GPM)	Reccomended Min. Feed Water Rate (gpm)	D
	240	325	0.65	1.95	
	120	323	0.65	1.95	
	240	256	0.51	1.52	
	120	250	0.31	1.52	
	240	433	0.87	2.6	
	120	455	0.87	2.0	С
	240	475	0.95	2.9	
	120	475	0.95	2.5	
	240	542	1.09	3.3	
	120	JHZ	1.05	5.5	-
	Steam			Safety Valve	
ng	Outlet	Water Feed	Drain Outlet	Outlet Size	
nt	Size (NPT)	Inlet Size (NPT)	Size (NPT)	(NPT)	В
	3/4" 1"	1/2"	1"	3/4"	D
	T				
n					
hts					
	1				

NAME	DATE	SUSS	MAN-AUTOMATIC CC	ORPORATION	
E.Z	4/24/20	4	43-20 34TH STREET, LONG ISLAND CITY, N	IEW YORK 11101	
х	х	TI	ſLE:		
ARE IN INCHES S: (EXCEPT AS NOTED) ± 1/64 1°			150psi, 380V, 415V, 480V &600V, 3ph		A
		B	ES85-ES18		
		S	CALE: 1:16	SHEET 2 OF 2	
2 1			1		